

# GP Plant Trailers

The Lfor Williams plant trailer range is designed specifically for transporting plant machinery and has been standard equipment for many plant users and plant hire firms since the 1980s. We offer three distinct types of plant trailer; The GP Range, described below and GX & GH Ranges (see overleaf):

The GP series trailers, widely regarded as the toughest plant trailers in the industry, have an open rectangular steel framework, integral with chassis. The GP range is our only plant trailer where the 16" wheel is an option, providing maximum off-road capability.

Maximum gross weight of the range is 3500kg. Models range from the smallest GP106 to the largest GP146. Trailers are offered with three tyre options and larger models are also available as tri-axle versions.

GP models are fitted with a tough resin-coated plywood platform. Various options are also available including factory fitted aluminium treadplate floor covering, bolt on ramp knife edge and 1.8m/6' skids or ramp in place of the standard size of 1.2m/4'.

All our plant trailer models are fitted with integrated ramp or skid supports. This standard feature ensures trailers are supported whilst being loaded without the need to deploy prop stands.

GP Trailers can be ordered with either low sides or high sides (see table above for dimensions). The axles on the low sided trailers are rear-set axles, and are particularly suitable for carrying excavators.

Low sided models are offered with either open or closed sides and have a bucket rest fitted as standard.

High sided models come with filled in sides, an optional bucket rest and axles which are more centrally positioned. This option is ideally suited to users who require flexible usage from their trailer; a reliable plant trailer providing higher sides for use as a general duty trailer.



GP106 low sided with optional open sides & 1.3m/4' skids



GP106 (see specification opposite)



GP126 (see specification opposite)



GP126 (see specification opposite)

## Size Combinations

Plant	Internal Width	Platform Length	Loading Height	Side Panel Height	
				Low	High
GP106	1785mm	3060mm/10'	430mm/1'5"	290mm/11"	410mm/16"
GP126	1785mm	3660mm/12'	430mm/1'5"	290mm/11"	410mm/16"
GP126 Tri	1785mm	3660mm/12'	410mm/1'4"	290mm/11"	410mm/16"
GP146 Tri	1785mm	4285mm/14'	410mm/1'4"	290mm/11"	410mm/16"


Loading heights will vary slightly depending on tyre options

# Trailer Features

It's the attention to detail of Ifor Williams trailers that makes our products so popular with owners. Just take a look at these standard features.



Chassis & Floor



Floor

## Chassis

The underside of the trailer features a galvanized steel chassis and drawbar, for long-lasting corrosion protection.

## Floor

Phenol-coated on both sides, our ply platform floors feature an embossed grip pattern on the upper surface.



Beam Axle



Spare Wheel

## Beam Axle & Leaf Spring Suspension

The Ifor Williams beam axle system increases stability and reliability whilst ensuring minimum maintenance.

## Spare Wheel

A mounting bracket and spare wheel are fitted as standard on most models.

## Coupling Head

The lockable low-profile coupling head ensures optimum clearance of 4x4 rear doors.



Coupling Head



Loading Skids

## Hinged Loading Skids

Fitted to the GP and GX models, these are adjustable for width when deployed.

# Optional Equipment

The addition of selected accessories allows you to further enhance your trailer, and tailor it to suit your specific needs.



## Perforated Steel Loading Skids

6'/1.83m & 8'/2.4m long steel loading ramps. A pair of prop stands are included to support the rear of the trailer when loading.



## Lightweight Aluminium Loading Skids

6'/1.83m & 8'/2.4m long aluminium loading ramps. A pair of prop stands are included to support the rear of the trailer when loading.



## Full Width Loading Ramp Kit

Can be fitted to LT/LM models with or without dropsides/ meshsides.



## Knife Edge for Ramp

Knife edges for ramps are available as a bolt-on optional extra for GX and GP plant trailers.



## Ladder Rack

Option available for LT/LM/CT/GD/GX and high sided GP models.



## Coupling Eye

Alternative coupling heads are available, 30mm, 40mm, 50mm and 76mm sizes. Please ask your Ifor Williams Distributor for further information.



## Headboard & Dropsides

Options available for LT/LM/CT range of trailers.

# Optional Equipment

Meshsides are available for most models, providing the capability to carry bulky loads such as hedge cuttings and waste packaging.



Canopies are available for most makes of 4x4 vehicle as well as being an option for some trailers. For more details please contact your local distributor.




## Lashing Straps

Lashing straps are used to secure and prevent movement of loads in the trailer.

## Prop Stands

Available for all models to give additional stability when loading and unloading. Plant trailers have integrated prop stands fitted to skids and ramps.



## Floorcovering

Aluminium treadplate.

## Lashing Ring

Recessed hinged ring providing a secure floor level fixing point.

## Braked Manual Winch

Manual 3 tonne winch (suitable for loading wheeled vehicles up to 3 tonne up an incline of 21°).

## Electric Winch

Powerful and robust electric winch complete with corded remote control unit.

# Plant Trailers

## GP Series

		165R13C 8PR Tyres	155/70R 12C Tyres	195/60R 12C Tyres	195/55R 10C Tyres	185/70R 13C Tyres	175/75R 16C Tyres	6.50R16C 10PR Tyres	Aluminium Treadplate Platform Covering	Weldmesh Panelled Side Extensions	Ladder Rack	Integrated Lashing Points	Walk-on Mudguards	Bucket Rest	Recessed Lashing Ring (pair)	Knife Edge for Ramp	Filled in Slides	12v/24v LED Lights	
	Maximum Gross Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight											
<b>GP-Low Sides</b>																			
GP106 Skids	3500kg	-	-	705kg	-	-	765kg	780kg	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
GP106 Ramp	3500kg	-	-	720kg	-	-	780kg	795kg	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
GP126 Skids	3500kg	-	-	780kg	-	-	840kg	855kg	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
GP126 Ramp	3500kg	-	-	795kg	-	-	855kg	870kg	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
GP126 Tri-Axle Skids	3500kg	-	-	890kg	-	-	980kg	-	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
GP126 Tri-Axle Ramp	3500kg	-	-	905kg	-	-	995kg	-	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
GP146 Tri-Axle Skids	3500kg	-	-	915kg	-	-	1005kg	-	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
GP146 Tri-Axle Ramp	3500kg	-	-	930kg	-	-	1020kg	-	Option	-	-	Std	Std	Std	Option	Option	Option	Option	
<b>GP-High Sides</b>																			
GP106H Skids	3500kg	-	-	785kg	-	-	845kg	860kg	Option	-	Option	Std	Std	Option	Option	Option	Std	Option	
GP106H Ramp	3500kg	-	-	800kg	-	-	860kg	875kg	Option	Option	Option	Std	Std	Option	Option	Option	Std	Option	
GP126H Skids	3500kg	-	-	870kg	-	-	930kg	945kg	Option	-	Option	Std	Std	Option	Option	Option	Std	Option	
GP126H Ramp	3500kg	-	-	885kg	-	-	945kg	960kg	Option	Option	Option	Std	Std	Option	Option	Option	Std	Option	
GP126H Tri-Axle Skids	3500kg	-	-	980kg	-	-	1070kg	-	Option	-	Option	Std	Std	Option	Option	Option	Std	Option	
GP126H Tri-Axle Ramp	3500kg	-	-	995kg	-	-	1085kg	-	Option	Option	Option	Std	Std	Option	Option	Option	Std	Option	
GP146H Tri-Axle Skids	3500kg	-	-	1095kg	-	-	1105kg	-	Option	-	Option	Std	Std	Option	Option	Option	Std	Option	
GP146H Tri-Axle Ramp	3500kg	-	-	1030kg	-	-	1120kg	-	Option	-	Option	Std	Std	Option	Option	Option	Std	Option	