

# GX Plant Trailers

**GX84** with ramp



**GX126** Tri-Axle with ramp



## Size Combinations

### Plant

	Internal Width	Platform Length	Loading Height	Side Panel Height
GX84	1250mm/4'2"	2450mm/8'	430mm/1'5"	270mm/11"
GX105	1575mm/5'2"	3030mm/9'11"	430mm/1'5"	270mm/11"
GX106	1840mm/6'	3030mm/9'11"	410mm/1'4"	270mm/11"
GX125	1575mm/5'2"	3660mm/12'	430mm/1'5"	270mm/11"
GX126	1840mm/6'	3660mm/12'	410mm/1'4"	270mm/11"

### GX Series

GX Series trailers are constructed from folded pregalvanized steel sections with filled-in sides for greater flexibility. The body design allows the machine operator to safely step down from the cab.

Trailers are offered with hinged adjustable skids or a full-width loading ramp. Trailers can be further enhanced by accessories such as a ladder rack, aluminium treadplate floor covering, mesh side extensions (only practical with full-width loading ramp), bolt-on ramp knife edge, and 1.8m/6' skids or ramp in place of the standard size of 1.2m/4'. The GX trailers come as standard with three pairs of integral lashing points attached to the body of the trailer.

GX Models are available with maximum gross weights of 2700kg and 3500kg.

All our plant models are fitted with integrated ramp and skid supports. This standard feature ensures trailers are supported whilst being loaded without the need to deploy prop stands.




GX range is available with meshsides (ramp model only)

# Trailer Features

It's the attention to detail of Ifor Williams trailers that makes our products so popular with owners. Just take a look at these standard features.



Chassis & Floor



Floor

## Chassis

The underside of the trailer features a galvanized steel chassis and drawbar, for long-lasting corrosion protection.

## Floor

Phenol-coated on both sides, our ply platform floors feature an embossed grip pattern on the upper surface.

## Beam Axle & Leaf Spring Suspension

The Ifor Williams beam axle system increases stability and reliability whilst ensuring minimum maintenance.

## Spare Wheel

A mounting bracket and spare wheel are fitted as standard on most models.

## Coupling Head

The lockable low-profile coupling head ensures optimum clearance of 4x4 rear doors.

## Hinged Loading Skids

Fitted to the GP and GX models, these are adjustable for width when deployed.



Beam Axle



Spare Wheel



Coupling Head



Loading Skids

# Optional Equipment

The addition of selected accessories allows you to further enhance your trailer, and tailor it to suit your specific needs.



## Perforated Steel Loading Skids

6'/1.83m & 8'/2.4m long steel loading ramps. A pair of prop stands are included to support the rear of the trailer when loading.



## Lightweight Aluminium Loading Skids

6'/1.83m & 8'/2.4m long aluminium loading ramps. A pair of prop stands are included to support the rear of the trailer when loading.



## Full Width Loading Ramp Kit

Can be fitted to LT/LM models with or without dropsides/ meshsides.



## Knife Edge for Ramp

Knife edges for ramps are available as a bolt-on optional extra for GX and GP plant trailers.



## Ladder Rack

Option available for LT/LM/CT/GD/GX and high sided GP models.



## Coupling Eye

Alternative coupling heads are available, 30mm, 40mm, 50mm and 76mm sizes. Please ask your Ifor Williams Distributor for further information.

# Optional Equipment

Meshsides are available for most models, providing the capability to carry bulky loads such as hedge cuttings and waste packaging.



## Lashing Straps

Lashing straps are used to secure and prevent movement of loads in the trailer.

## Prop Stands

Available for all models to give additional stability when loading and unloading. Plant trailers have integrated prop stands fitted to skids and ramps.



## Floorcovering

Aluminium treadplate.

## Lashing Ring

Recessed hinged ring providing a secure floor level fixing point.

## Braked Manual Winch

Manual 3 tonne winch (suitable for loading wheeled vehicles up to 3 tonne up an incline of 21°).

## Electric Winch

Powerful and robust electric winch complete with corded remote control unit.

Canopies are available for most makes of 4x4 vehicle as well as being an option for some trailers. For more details please contact your local distributor.







GX106 with skids

# Plant Trailers

## GX Series

		165R13C 8PR Tyres	155/70R 12C Tyres	195/60R 12C Tyres	195/55R 10C Tyres	185/70R 13C Tyres	175/75R 16C Tyres	6.50R 16C 10PR Tyres	Aluminium Treadplate Platform Covering	Weldmesh Panelled Side Extensions	Ladder Rack	Integrated Lashing Points	Walk-on Mudguards	Bucket Rest	Recessed Lashing Ring (pair)	Knife Edge for Ramp	Filled in Slides	12v/24v LED Lights
	Maximum Gross Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight										
GX84 Skids	2700kg	540kg	-	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX84 Ramp	2700kg	540kg	-	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option
GX85 Skids	2700kg	590kg	-	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX85 Ramp	2700kg	635kg	-	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option
GX105 Skids	2700kg	660kg	-	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX105 Ramp	2700kg	675kg	-	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option
GX105 H/D Skids	3500kg	-	670kg	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX105 H/D Ramp	3500kg	-	690kg	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option
GX125 H/D Skids	3500kg	-	740kg	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX125 H/D Ramp	3500kg	-	760kg	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option
GX106 Skids	3500kg	-	700kg	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX106 Ramp	3500kg	-	715kg	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option
GX126 Skids	3500kg	-	765kg	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX126 Ramp	3500kg	-	795kg	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option
GX126 Tri-Axle Skids	3500kg	-	875kg	-	-	-	-	-	Option	-	Option	Std	Std	Std	Option**	Option	Std	Option
GX126 Tri-Axle Ramp	3500kg	-	890kg	-	-	-	-	-	Option	Option	Option	Std	Std	Std	Option**	Option	Std	Option