

# LM/LT Flatbed Trailers



LM146 with optional dropsides, tailboard, headboard, lashing straps & ladder rack





## LM/LT Flatbed Trailers

From the smallest LT85 to the largest LM208, all flatbed models are built around a welded steel, galvanized chassis fitted with bolt-on tapered drawbars and the Ifor Williams beam axle and leaf sprung suspension.

Whenever there's work to be done you'll find a flatbed model to help you do it. Our flatbed trailers epitomise the flexibility of our commercial range. Purchasers from roofers to gardeners, small businesses to local authorities have all found that this range of trailers can carry heavy or bulky loads with ease.

The flatbed range is offered in width options ranging from 1.52m/5' to 2.5m/8'2" and length options from 2.44m/8' to 6.1m/20'.

The maximum gross weight for the LT model is 2000kg, whilst the heavier LM models offer between 2700kg and 3500kg.



**LM166** Tri-axle with optional headboard, electric winch, loading skids, propstands and lashing straps



### Skid rail & holder

The LT/LM range feature a skid mounting rail and skid holder built into the rear of the trailer (1.83m/2.44m or 6'/8' skids are optional extras).

# Flatbed Trailers continued

Normally supplied with twin axles. Tri-axle options are available on our LM6 and LM7 series models (except LM106 & LM127). The LM206, LM207 and LM208 are only available as tri-axle trailers.

Tough, adaptable and easy to maintain, all models are fitted with a tough resin-coated plywood platform as standard. An option of aluminium treadplate covering is available, along with recessed lashing rings. Trailers can be further enhanced with accessories such as a headboard, ladder rack, dropsides or meshside extensions.

With the addition of a winch, rear propstands and either loading skids or the full-width ramp (1.83m/6' in length), the versatile flatbed can be used to carry loads, such as smallplant, ride-on mowers, mixers, shredders, rollers and a multitude of mobile plant equipment.



LT85 with optional dropsides, tailboard, headboard & ladder rack



## Size Combinations

### Flatbed

	Platform Width	Platform Length	Loading Height	Dropside Height
LT/LM85	1525mm/5'	2440mm/8'	620mm/2'	352mm/1'2"
LT/LM105	1680mm/5'5"	3010mm/9'9"	620mm/2' 640mm/2'1"	352mm/1'2"
LT/LM106	1980mm/6'5"	3010mm/9'10"	620mm/2' 640mm/2'1"	352mm/1'2"
LT/LM125	1680mm/5'5"	3620mm/11'10"	620mm/2' 640mm/2'1"	352mm/1'2"
LT/LM126	1980mm/6'5"	3620mm/11'10"	620mm/2' 640mm/2'1"	352mm/1'2"
LM127	2250mm/7'4"	3620mm/11'10"	640mm/2'1"	352mm/1'2"
LT/LM146	1980mm/6'5"	4230mm/13'10"	620mm/2' 640mm/2'1"	352mm/1'2"
LM147	2250mm/7'4"	4230mm/13'10"	640mm/2'1"	352mm/1'2"
LM166	1980mm/6'5"	4770mm/15'8"	670mm/2'2"	352mm/1'2"
LM167	2250mm/7'4"	4770mm/15'8"	670mm/2'2"	352mm/1'2"
LM186	1980mm/6'5"	5470mm/17'11"	670mm/2'2"	352mm/1'2"
LM187	2250mm/7'4"	5470mm/17'11"	670mm/2'2"	352mm/1'2"
LM206	1980mm/6'5"	6100mm/20'	670mm/2'2"	352mm/1'2"
LM207	2250mm/7'4"	6100mm/20'	670mm/2'2"	352mm/1'2"
LM208	2550mm/8'	6100mm/20'	670mm/2'2"	352mm/1'2"





LM146 with optional headboard, dropsides, meshsides, full-width loading ramp, propstands and manual winch (see opposite)



# Trailer Features

It's the attention to detail of Ifor Williams trailers that makes our products so popular with owners. Just take a look at these standard features.



Chassis & Floor



Floor

## Chassis

The underside of the trailer features a galvanized steel chassis and drawbar, for long-lasting corrosion protection.

## Floor

Phenol-coated on both sides, our ply platform floors feature an embossed grip pattern on the upper surface.

## Beam Axle & Leaf Spring Suspension

The Ifor Williams beam axle system increases stability and reliability whilst ensuring minimum maintenance.

## Spare Wheel

A mounting bracket and spare wheel are fitted as standard on most models.

## Coupling Head

The lockable low-profile coupling head ensures optimum clearance of 4x4 rear doors.

## Hinged Loading Skids


Fitted to the GP and GX models, these are adjustable for width when deployed.



Beam Axle



Spare Wheel



Coupling Head



Loading Skids

# Optional Equipment

The addition of selected accessories allows you to further enhance your trailer, and tailor it to suit your specific needs.



## Perforated Steel Loading Skids

6'/1.83m & 8'/2.4m long steel loading ramps. A pair of prop stands are included to support the rear of the trailer when loading.



## Lightweight Aluminium Loading Skids

6'/1.83m & 8'/2.4m long aluminium loading ramps. A pair of prop stands are included to support the rear of the trailer when loading.




## Full Width Loading Ramp Kit

Can be fitted to LT/LM models with or without dropsides/ meshsides.



## Knife Edge for Ramp

Knife edges for ramps are available as a bolt-on optional extra for GX and GP plant trailers.



## Ladder Rack

Option available for LT/LM/CT/GD/GX and high sided GP models.



## Coupling Eye

Alternative coupling heads are available, 30mm, 40mm, 50mm and 76mm sizes. Please ask your Ifor Williams Distributor for further information.



## Headboard & Dropsides

Options available for LT/LM/CT range of trailers.

# Optional Equipment

Meshsides are available for most models, providing the capability to carry bulky loads such as hedge cuttings and waste packaging.



Canopies are available for most makes of 4x4 vehicle as well as being an option for some trailers. For more details please contact your local distributor.



## Lashing Straps

Lashing straps are used to secure and prevent movement of loads in the trailer.

## Prop Stands

Available for all models to give additional stability when loading and unloading. Plant trailers have integrated prop stands fitted to skids and ramps.



## Floorcovering

Aluminium treadplate.

## Lashing Ring

Recessed hinged ring providing a secure floor level fixing point.

## Braked Manual Winch

Manual 3 tonne winch (suitable for loading wheeled vehicles up to 3 tonne up an incline of 21°).

## Electric Winch

Powerful and robust electric winch complete with corded remote control unit.

# LT/LM Trailer Specifications

## LT Series

	Maximum Gross Weight	Tyres	Trailer Fitted with Resin Coated Plywood Platform	Aluminium Treadplate Floor Covering	Removable Headboard, Dropsides & Tailboard	Removable Headboard	Removable ladder rack (Headboard Required)	1.8m/6' Long Perforated Galvanized Steel Skids (Pair) (Including Prop Stands)	1.8m/6' Long Aluminium Skids (Pair) (Including Prop Stands)	2.4m/8' Long Perforated Galvanized Steel Skids (Pair) (Including Prop Stands)	2.4m/8' Long Aluminium Skids (Pair) (Including Prop Stands)	Weldmesh Panelled Side Extensions	Recessed Lashing Ring (pair)	6' Full Width Loading Ramp (Including Prop Stands)	Lashing Straps (3m & 8m)	12V/24v LED Lights
	Unladen Weight															
LT85	2000kg	145/70R13C	450kg	Option	Option	Option	Option	Option	Option	-	-	Option <sup>††</sup>	Option	Option	Option	Option
LT105	2000kg	145/70R13C	510kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LT125	2000kg	145/70R13C	565kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LT106	2000kg	145/70R13C	555kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LT126	2000kg	145/70R13C	615kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LT146	2000kg	145/70R13C	660kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
<b>LM 5-Series</b>																
LM85	2700kg	195/60R12C	495kg	Option	Option	Option	Option	Option	Option	-	-	Option <sup>††</sup>	Option	Option	Option	Option
LM105	2700kg	195/60R12C	575kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM125	2700kg	195/60R12C	620kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
3500kg Gross version available (add 30kg)																
<b>LM 6-Series</b>																
LM106	3500kg	195/60R12C	620kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM126	3500kg	195/60R12C	675kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM146	3500kg	195/60R12C	735kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM166	3500kg	195/60R12C	795kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM186	3500kg	195/60R12C	855kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM206 Tri	3500kg	195/60R12C	1010kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	-	Option	Option
Tri-axle version on 12', 14', 16' & 18' models (add 110kg)																
<b>LM 7-Series</b>																
LM127	3500kg	195/60R12C	705kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM147	3500kg	195/60R12C	775kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM167	3500kg	195/60R12C	845kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM187	3500kg	195/60R12C	915kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	Option	Option	Option
LM207 Tri	3500kg	195/60R12C	1090kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	-	Option	Option
LM208 Tri	3500kg	195/60R12C	1200kg	Option	Option	Option	Option	Option	Option	Option	Option	Option <sup>††</sup>	Option	-	Option	Option
Tri-axle version on 14', 16' & 18' models (add 110kg)																

## Other optional extras

Braked Manual winch 3000kg  
 Electric winch  
 (Manual winch not available on CT models)

Optional accessories have been priced as factory fit items, ordered with your trailer. If ordered at a later date, your distributor may need to fit the items, which will result in fitting charges being incurred.

\* Excludes tailboard: a standard ramp (1') is included within the trailer price.

†† Headboard, dropsides and tailboard required to fit meshsides.